

EFC-985 FASTENING PLYWOOD TO E-BEAM
ITEM # 56896

FASTENING PLYWOOD TO E-BEAM

Select the appropriate **FASTENER** for your **Application**

	FASTENER	PULL-OUT-FORCE	SIZE	FASTENER
SINGLE POUR (YELLOW)	E-BEAM Nail (Yellow) (#4 Box, 1,000/box) **EFCO ITEM #10890**	160 lb (73 kg)	.100" x 1 1/2" (2.5 mm x 38 mm)	
MULTIPLE POURS (GREEN)	E-BEAM Nail (Green) (#4 Box, 1,000/box) **EFCO ITEM #12890**	410 lb (186 kg)	.100" x 1 1/2" (2.5 mm x 38 mm)	
	E-BEAM Nail (Green Collated) (250/coil 4,000/box) **EFCO ITEM #09890**	410 lb (186 kg)	.100" x 1 1/2" (2.5 mm x 38 mm)	
FASTENERS PULLS THROUGH PLYWOOD (RED)	Self-Drilling T25 Screw 1 3/4" (45 mm) 4000/Box Quick Guard® Coating **EFCO ITEM #20890** T25 6-lobe Drive	500 lb (228 kg)	#10-16 x 1 3/4" (M5 x .08 mm x 45 mm)	
	Self-Drilling T25 Collated Screw 1 3/4" (45 mm) 2000/Box Quick Guard® Coating **EFCO ITEM #21890** T25 6-lobe Drive	500 lb (228 kg)	#10-16 x 1 3/4" (M5 x .08 mm x 45 mm)	

AVAILABLE THROUGH EFCO







T25 6-LOBE DRIVER

PRO250G2 SUBFLOOR SYSTEM FOR COLLATED SCREWS (ITEM# 21890)
AVAILABLE CORDLESS OR CORDED
CONTACT: SIMPSON STRONG-TIE® 1-800-999-5099




FASCO NAIL GUN FOR COLLATED NAILS (ITEM# 09890)
MODEL F44AC CN15W-PS65
CONTACT: 1-800-239-8665



METABO HPT (HITACHI) NAIL GUN FOR COLLATED NAILS
(ITEM# 09890)
MODEL NV65AH2M




MULTIPLE-POUR NAILING PATTERN



RECOMMENDED NAILING PATTERNS FOR PLYWOOD FACING ON E-BEAM WALL AND ELEVATED DECK SOLUTIONS

FASTENER POSITIONS



SINGLE-POUR NAILING PATTERN

Ref: Plywood to a pine wood nailer strip with a deck screw will pull-out at 306 lb (138.8 kg).
Note: Pull-out loads are EFCO laboratory results and do not include a safety factor.

EFCO'S E-BEAM joist is made of lightweight galvanized steel and uses no wood nailer strip. Use either nails or screws to attach a sheet of plywood to the steel joist.